
Technical Product Sheet

Packaged Window Heat Pump Product Highlights:

- Highly efficient 9k BTU package windowmounted heat pump(PWHP) from the world's #1 air treatment brand
- Cold climate inverter heat pump technology with operation down to -13°F
- Adjustable saddle-style construction to work with various window and wall construction types
- Pivoting outdoor section with included liftassisted mounting bracket for easy installation
- No auxiliary resistance electric heater
- Self-contained condensate management system that does not require condensate drain/ plumbing
- Compatible with standard 15A-120VAC outlet
- Models available with with wireless mesh BACnet capability or Wi-Fi
- Quiet Operation
- R-32 refrigerant
- Limited Warranty: 2 year full (5 year functional and sealed system parts; 12 year compressor)
- Email: pwhpsales@midea.com



Min Window dimensions

	Outdoor Condition	Capacity (BTU/hr)	Efficiency
Cooling Mode	95 °F (35 °C)	9010	11.81 EER
	47 °F (8.3 °C)	9000	4.0 COP
Heating Mode	17 °F (-8.3 °C)	9000	2.42 COP
	5 °F (-15 °C)	9000	2.0 COP
Min Temp	-13 °F (-25 °C)	5050	1.41 COP
CEER	16		
SEER2	18.76		
HSPF2	10.12		
Indoor Sound	High	Low	Silent
Pressure Level	51 dB(A)	43 dB(A)	29 dB(A)
Unit Weight	130 lbs		



